

CHOICE OF ACCOMMODATION

Inquire with the hotel in advance (even if the hotel pretends to be accessible/ to have wheelchair adapted rooms) to check accessibility of the hotel in general, and in particular:

- ✓ **Entrance** without steps and if there are stairs, but if a ramp is foreseen, check if ramp is not too steep (tolerated slope is 5%).
 - Entrance door and interior doors should be 85 cm width;
 - Sliding doors should be 110 cm width.
- ✓ **Accessible toilets:** the minimal legal dimensions are 150 x 150 cm with a rotation space of 150 cm diameter and:
 - A free space of 110 cm is foreseen in the direction of the door;
 - The toilet should be installed at 50 cm high;
 - 2 Folding handles independent from each other of 90 cm length should be placed at 80 cm high at 35 distances from the toilet;
 - Big closed bin for sanitary towels for incontinent people.

✓ Lifts:

- Command systems should be perceptible for all people with disabilities by vocal and light signals;
- Lift button outside the lift should be installed at around 80 cm high;
- There should be a manoeuvring space of 150 cm diameter in front of the lift door;
- Door width should be 90 cm;
- Measures: 140 cm deep and minimum 110 cm broad.

✓ Accessible dining and breakfast room

✓ Room:

- There should be free moving space of 90 cm around all furniture;
- Rotation space of 150 cm;
- Cupboard with cloth hangers on 130 cm height maximum.

✓ Bathroom in the room:

- · Rotation area of 150 cm;
- Preferably a roll-in shower (without border) with little inclines on the ground, with folding chair installed on 50 cm high, with a seat of 40 x 50 cm minimum, and folding grips of 90 cm long, situated at 35 cm of the axe of the seat and installed at 80 cm eighth;
- Bath: h = 50 cm, approaching area of 80 cm next the bath. At one of the extremities of the bath, there should be a transfer plan of 60 cm over the total width of the bath. Next to the transfer plan there should be a grip of 80 cm long at 70 h of the ground.